

A					
B	CKT	DIM A	DIM B	DIM C	
	4	3.00	5.03	11.10	
	5	4.00	6.03	12.10	
	6	5.00	7.03	13.10	
	7	6.00	8.03	14.10	
	8	7.00	9.03	15.10	
	9	8.00	10.03	16.10	
	10	9.00	11.03	17.10	
	11	10.00	12.03	18.10	
	12	11.00	13.03	19.10	
	13	12.00	14.03	20.10	
	14	13.00	15.03	21.10	
	15	14.00	16.03	22.10	
	16	15.00	17.03	23.10	
	17	16.00	18.03	24.10	
	18	17.00	19.03	25.10	
	19	18.00	20.03	26.10	
	20	19.00	21.03	27.10	
	21	20.00	22.03	28.10	
	22	21.00	23.03	29.10	
23	22.00	24.03	30.10		
24	23.00	25.03	31.10		
25	24.00	26.03	32.10		
26	25.00	27.03	33.10		
27	26.00	28.03	34.10		
28	27.00	29.03	35.10		
29	28.00	30.03	36.10		
30	29.00	31.03	37.10		
31	30.00	32.03	38.10		
32	31.00	33.03	39.10		
33	32.00	34.03	40.10		
34	33.00	35.03	41.10		
35	34.00	36.03	42.10		
36	35.00	37.03	43.10		
37	36.00	38.03	44.10		
38	37.00	39.03	45.10		
39	38.00	40.03	46.10		
40	39.00	41.03	47.10		
C					

技术指标 (Technical Index):

1. 塑件表面应光洁, 无毛边、无明显收缩、缺陷、裂纹等现象。
(The surface of the plastic parts should be smooth, no rough edges, no obvious shrinkage, defects, cracks and other phenomena.)

2. 温度范围 (Temperature range): -25° C~+85° C.

3. 额定电压 (Rated voltage): 50V, AC/DC (=等效).

4. 接触电阻 (Contact resistance): ≤0.03Ω.

5. 绝缘电阻 (Insulation resistance): ≥5000Ω.

E										
F										

序号	品名	材质	设计/Designed	审核/Checked	批准/Approved	比例	规格型号/ Part No	物料号/ Part No
1	1. OK 型卧式 (H2, S) 1. OK Type Housing	LCP UL94V-0 本色 Natural	设计/Designed	审核/Checked	批准/Approved	1:1	1.0-H2.5K型卧式上接	TS-Q002***
2	1. OK 型上接端子 (H2, S) 1. OK Type Upper Terminal	铜合金/表面镀锡 Copper Alloy/ Tin Plating	设计/Designed	审核/Checked	批准/Approved	1:1	1.0-H2.5K型卧式上接	TS-Q002***
3	1. OK 型卧式 (H2, S) 1. OK Type Actuator	LCP UL94V-0 黑色 Black	设计/Designed	审核/Checked	批准/Approved	1:1	1.0-H2.5K型卧式上接	TS-Q002***
4	1. OK 型卧式 (H2, S) 1. OK Type Fillet Nail	铜合金/表面镀锡 Copper Alloy/ Tin Plating	设计/Designed	审核/Checked	批准/Approved	1:1	1.0-H2.5K型卧式上接	TS-Q002***

备注

吴永余 吴东升 何春林

温州瀚精电子有限公司
WENZHOU HANJING ELECTRONIC CO., LTD.